



Smart
Connect

OUTDOOR CAMERA WITH SPOTLIGHT

EN - WI-FI OUTDOOR SECURITY CAMERA,
WITH SPOTLIGHT

NL - WI-FI OUTDOOR BEVEILIGINGSCAMERA,
MET SPOT

FR - CAMÉRA DE SÉCURITÉ EXTÉRIEURE WI-FI,
AVEC PROJECTEUR

DE - WLAN-ÜBERWACHUNGSKAMERA
FÜR DEN AUBENBEREICH,
MIT SCHEINWERFER

PL - WI-FI ZEWNETRZNA KAMERA
BEZPIECZENSTWA,
Z REFLEKTOREM

CZ - WI-FI VENKOVNÍ BEZPEČNOSTNÍ KAMERA,
S REFLEKTOREM

IT - WI-FI TELECAMERA DI SICUREZZA DA ESTERNO,
CON RIFLETTORE

SK - WI-FI VONKAJŠIA BEZPEČNOSTNÁ KAMERA,
S REFLEKTOROM

ES - CÁMARA DE SEGURIDAD WI-FI OUTDOOR,
CON FOCO

PT - CÁMERA DE SEGURANÇA WI-FI OUTDOOR,
COM HOLOFOTES



Art. No. 3012979

Action Service & Distributie B.V.
Poperenmarkt 15, 1621 PG Zwaagwijk, Oost (NL)

www.lsc-light.com

Made in China



This product is intended for separate collection
in a designated collection point. Do not dispose of
this product with the household waste. For further
information, please contact your local authorities.

Recycled items are putting into service.
See manual.

38 25 00 04 00 A1



8 712879 156901 >

Specifications

Power supply

Input: 220-240 V AC, 50/60 Hz
Output: DC 12V/1A

Batteries required / supplied

No
12V/1A EURO PLUG AC Charger

Adapter included

3.5mm DC power jack

Cable specs (m)

1.3 meters on the charger

Extension cable

3 meters on the camera

Wattage (W - Rated Power)

12w

Voltage (V)

1a

Current (mA)

50/60

Frequency (Hz)

50/60

Storage

Build-in SD card(Max.128G), Cloud storage

Camera image resolution

2mp CMOS Sensor

Motion sensor

by FW

Sensor specs

2mp CMOS Sensor

Nightvision

Yes

IR distance

Night visibility up to 8 meters

Pan/tilt function

6pcs

Privacy function

N/A

Two way audio (Y/N)

YES

Microphone specs

yes

Built in speaker

-38db

Speaker specs

yes

Adjustable volume

1w, Yes to switch the mobile volume

IP value

IP65

Operating temperature

-20 °C to 50 °C

Camera

Image sensor

1080P Color Sensor 1/2.9"CMOS

Shutter

1/25~1/100,000 per second

Audio input/output

Built-in microphone and speaker

Lens

4mm

Angle of view

100°

Vertical angle of view

55°

Horizontal angle of view

90°

Day & night

Electronic(IR-CUT filter with auto switch)

WDR

Digital WDR

Compression Standard

Video compression

H.264

16Kbps~2Mbps

Bit rate

Yes

Dual stream

Yes

Image

Image resolution 1080P(1920*1080)

Min illuminance Color 0.01Lux@F1.2

Black and White 0.001Lux@F1.2

Support HD/SD,support flip

FW default 15fps

Image setting

Frame rate

FW default 15fps

Network

Alarm trigger Intelligent motion detection

Yes

Area control detection zone

Yes

Wireless Security 64/128-bit WPA/WPA2, WPA-PSK/WPA2-PSK, WPS

Communication Protocol TCP/IP,HTTP,DHCP,DNS

Interface protocol Private

Wireless 2.4G WIFI(IEEE802.11b/g/n)

Supported mobile phone OS iOS 8 up,Android 4.2 up

Data Security AES128

Wi-Fi

Frequency Range 2.4G Wifi

Antenna Gain 2.0 db

Max. Radio Transmission Power 17dbm