





## PRODUCT DATASHEET

<b>Brandname</b>	LSC
<b>Product description</b>	LSC Ball P45 Softline RA95 Straight filament 220-240V 4,9W 470lm 2900K E14 dimmable via LED dimmer
<b>EAN Code</b>	8712879162056
<b>Product code</b>	3206550 (factory model number: DSD Qa-sF-LD y2 z (11006) / A60-F-LD-URA 4.9W Milky 2900K)

### Type of light source

Lighting technology used	LED	Non-directional or directional	Non-directional
Mains or non-mains	Mains	Connected light source (CLS)	No
Colour tuneable light source (CTLS)	No	Envelope	No
High luminance light source	No	Dimmable	Dimmable via LED dimmer
Anti-glare shield	No	Lamp holder fitting type/size	E14

### General product parameters

Energy consumption in on-mode	5 kWh/1000h	Energy efficiency class	F
Useful luminous flux ( $\Phi_{use}$ )	470 lm	Measured in	Sphere (360°)
Colour temperature (CCT)	2900 K	Declared lifetime ( $L_{70B50}$ )	15000 hr
On-mode power ( $P_{on}$ )	4.9 W	Standby power ( $P_{sb}$ )	-
Network standby power ( $P_{net}$ )	-	Colour rendering index (CRI)	95
Claim of equivalent power	Yes	Equivalent power (W)	40 W
Voltage (V)	220-240 V	Frequency (Hz)	50/60 Hz
Chromaticity coordinate x	0.4440	Chromaticity coordinate y	0.4070
Product height	75 mm	Spectrum	
Product length	-		
Product width	45 mm		
Product diameter	45 mm		

### Product parameters for LED & OLED light sources

R9 colour rendering index value	96	Survival factor	-
Lumen maintenance factor	0.93		
Displacement factor ( $\cos \phi_1$ )	0.7	Colour consistency in MacAdam ellipse (SDCM)	$\leq 6$ steps MacAdam ellipse
LED light source replaces a fluorescent light source	Not applicable		
Flicker metric ( $P_{st LM}$ )	0.9	Stroboscopic effect metric (SVM)	0.4